

reveal -styles.txt

<!-- Paste this into Content Editor Web Part with Source Editor to show CSS class of hovered areas -->

```
<script language="javascript">
function IDInfo()
{
    if (window.event.srcElement.tagName != null)
    {
        ststag.innerHTML = "<" + window.event.srcElement.tagName + ">";
    }
    else
    {
        ststag.innerHTML = "";
    }

    if (window.event.srcElement.id != null)
    {
        stsid.innerHTML = window.event.srcElement.id;
    }
    else
    {
        stsid.innerHTML = "";
    }
    if (window.event.srcElement.name != null)
    {
        stsname.innerHTML = window.event.srcElement.name;
    }
    else
    {
        stsname.innerHTML = "";
    }
    if (window.event.srcElement != null)
    {
        var currElem = window.event.srcElement;
        var classTree = '';
        do
        {
            if (currElem.className != null && currElem.className != '')
            {
                if (classTree != '')
                {
                    classTree = currElem.className + "->" + classTree;
                }
                else
                {
                    classTree = currElem.className;
                }
            }

            currElem = currElem.parentElement;
        } while (currElem != null);
        stsclass.innerHTML = classTree;
    }
    else
    {
        stsclass.innerHTML = "";
    }
}
}
```

window.document.body.onmouseover = IDInfo; </script>

<div style="border-style:solid;border-width:1px;width:350px;height:175px;position:absolute;left:300px;top:200px;z-index:15;padding-left:4px;

reveal -styles.txt

```
padding-right: 4px; padding-top: 2px; padding-bottom: 2px; background-color: #EEEEF4">
<p id="ststagtitle"><font face="Tahoma" id="ststagtitle">Tag: </font>
<font face="Tahoma" id="ststag">&#xa0; </font>
</p>
<p id="stsidtitle"><font face="Tahoma" id="stsidtitle">ID: </font>
<font face="Tahoma" id="stsid">&#xa0; </font>
</p>
<p id="stsnametitle"><font face="Tahoma" id="stsnametitle">Name: </font>
<font face="Tahoma" id="stsnam">&#xa0; </font>
</p>
<p id="stsclasstitle"><font face="Tahoma" id="stsclasstitle">Class: </font>
<font face="Tahoma" id="stsclass">&#xa0; </font>
</p>
</div>
```